



Standard



Adjusting program (CAL):
For quick setting of the balance's accuracy. External adjusting weight required.



Rechargeable battery pack:
rechargeable set.



Mains adapter: 230 V/50Hz in standard version for Germany. On request GB, AUS or USA version.



Tare: put back displayed value to „0“ during weighing process, e.g. to add or remove weighing material from a container

Order Hotline:
Go to back page of catalogue

Compact up to 600 kg

KERN HUS
Crane scale



Loop
steel, nickel-plated. Aperture approx. 24 mm wide



STANDARD



Backlit LCD display
digit height 23 mm



Adjusting program CAL
External test weights at an additional price



Rechargeable battery pack
internal standard, operating time approx. 120 h, charging time approx. 8 h with mains adapter. Selectable: AUTO-OFF function after 4 min without a change of load to preserve the battery



Infrared remote control
standard.
Range approx. 2.5 m.
All functions are selectable. WxDxH 120x60x15 mm

Ready for use
Batteries size AAA (2x 1.5 V) included



Tare:
Resets the display to "0" when there is a load on the scale. Now removed or added loads are directly displayed

Data hold function
the weight display can be "frozen" using the HOLD-key until another key is pressed

Housing
WxDxH 150x140x155mm, total height from loop to hook 360 mm (HUS 600: 380 mm)

Charge condition indicator
using LED visual display

Hook
with safety catch. Steel, nickel-plated, revolving. Aperture approx. 20 mm (HUS 600 approx. 24 mm)

Price reduction

Model	Weighing range Max kg	Read-out d g	OPTION Certificate KERN DKD
KERN HUS 60K 20	60	20	963-129
HUS 150K 50	150	50	963-129
HUS 300K 100	300	100	963-129
HUS 600K 200	600	200	963-130

